









SPECIFICATIONS

ENGINE

Model Single cylinder, naturally-aspirated,

water-cooled engine

Engine capacity 611cc Fuel injection DI

Max. output 11.3hp @ 3000rpm

Max. torque 3.16mkg @ 1600-1800rpm

Fuel tank capacity 10 litres

CLUTCH AND TRANSMISSION

Single plate, dry friction diaphragm Clutch

TA59, Synchromesh 4 + 1 Gearbox Mechanical rack & pinion Steering

SUSPENSION

Front MacPherson strut

Coil spring with semi-trailing arm Rear


and hydraulic telescopic shock absorbers

BRAKES

Powerful Water Cooled Engine

Hydraulic drum Front Hydraulic drum Rear

Stylish Dashboard



High Mileage & Low Maintenance Cost



Attractive Exteriors

Service outlets

WHEELS & TYRES

DIMENSION (IN MM)

145/80 R 12 LT 6PR

Load body dimensions

WEIGHTS (IN KG)

PERFORMANCE

TATA ADVANTAGE

Turning circle radius

Wheelbase

Front track

Rear track

Kerb weight

Gradeability

Width

Length

Height

GVW

Payload



Spacious Cabin & Comfortable Seats

1650

1480

3020

1800

1256

1316

3.5m

1285

685

600

22%

1685 x 1480 x 400



Over 1200 outlets across India



Safe



For further details, please contact: Tata Motors Limited, Commercial Vehicles Business Unit, 20th Floor, Tower 2. One Indiabulls Centre, 841, Senapati Bapat Marg, Mumbai - 400 013. Tel: (022) 6658 6000 Fax: (022) 6658 6010 Toll-free: 1800 209 7979 Website: http://acezip.tatamotors.com/ or SMS* <ACEZIP> to 5616161

The illustrations and photographs may show accessories and items of optional equipment which are not part of standard specifications. Due to printing processes, colours may vary slightly from those shown. All listed specifications are current and subject to change or upgrade without prior notice, in accordance with the company's policy of continuous improvement.

To know more, give us a missed call on 080-30636006

*SMS charges as per the service provider



